

PORTABLE FIRE EXTINGUISHERS

ABC Powder Fire Extinguisher, 4 kg

Stored-pressure 4 kg ABC powder cylinder rated 27A 144B C under EN 3-7 with CNBOP-PIB approval, with metal hook wall hanger for boiler rooms, garages, and workshops.



- 27A 144B C on a 4 kg charge
- Metal hook wall hanger on every unit
- Boiler rooms, garages, and workshops
- Approved to 1000 V

SPECIFICATIONS

Manufacturer model	GP-4x ABC/MP	Dimensions	463 mm high, 140 mm cylinder diameter
Fire rating	27A 144B C	Gross weight	6.8 kg
Capacity	4 kg	Mounting	Metal hook wall hanger included
Extinguishing medium	ABC dry powder	Warranty	2 years from date of manufacture
Standard	EN 3-7 (CNBOP-PIB approved)	Manufacture	Manufactured in Poland
Operating temperature	-30 °C to +60 °C	Article number	NV-FE-104
Electrical safety	Live equipment to 1000 V	EAN	5907620600403

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY			
8424.10	EXW · FCA · DAP	CE	EN 3-7	CNBOP-PIB	ISO 9001

PRODUCT OVERVIEW

Polish-manufactured stored-pressure ABC powder extinguisher from OGNIOCHRON S.A., model GP-4x ABC/MP, sized for boiler rooms, garages, and home workshops where buyers want a mid-size workplace portable that an adult can operate without specialist training. The 4 kg charge is rated 27A 144B C under EN 3-7 with CNBOP-PIB approval, approved for live electrical equipment up to 1000 V, and operates from -30 °C to +60 °C. Each unit ships with a metal hook wall hanger so it can be fixed at the hazard point rather than left on the floor. At 6.8 kg gross weight and 463 mm high it sits between the 1 kg supplementary line and the 6 kg full workplace cylinder for plant rooms where space or lifting limits favour a lighter charge.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

