

PORTABLE FIRE EXTINGUISHERS

ABC Powder Fire Extinguisher, 6 kg

Stored-pressure 6 kg ABC powder cylinder rated 55A 233B C under EN 3-7, with metal hook wall hanger for boiler rooms, garages, and workshops where a full workplace rating is required.



- 55A 233B C on a 6 kg charge
- Metal hook wall hanger on every unit
- Boiler rooms, garages, and workshops
- 2 years from date of manufacture

SPECIFICATIONS

Manufacturer model	GP-6x ABC/MP	Dimensions	495 mm high, 160 mm cylinder diameter
Fire rating	55A 233B C	Gross weight	9.3 kg
Capacity	6 kg	Mounting	Metal hook wall hanger included
Extinguishing medium	ABC dry powder	Warranty	2 years from date of manufacture
Standard	EN 3-7	Manufacture	Manufactured in Poland
Operating temperature	-30 °C to +60 °C	Article number	NV-FE-106
Electrical safety	Live equipment to 1000 V	EAN	5907620600557

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY			
8424.10	EXW · FCA · DAP	CE	EN 3-7	CNBOP-PIB	ISO 9001

PRODUCT OVERVIEW

Polish-manufactured stored-pressure ABC powder extinguisher from OGNIOCHRON S.A., model GP-6x ABC/MP, sized for boiler rooms, garages, and workshops where buyers need the highest practical powder rating in a portable they can operate without specialist training. The 6 kg charge is rated 55A 233B C under EN 3-7, approved for live electrical equipment up to 1000 V, and operates from -30 °C to +60 °C. Each unit ships with a metal hook wall hanger so it can be fixed at the hazard point rather than left on the floor. At 9.3 kg gross weight and 495 mm high it is the standard workplace cylinder for domestic plant rooms and light industrial bays where a 1 kg supplementary unit would not meet the calculated rating.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

