

PORTABLE FIRE EXTINGUISHERS

ABC Powder Fire Extinguisher, 9 kg

Stored-pressure 9 kg ABC powder cylinder rated 55A 233B C under EN 3-7 with CNBOP-PIB approval, with metal hook wall hanger for boiler rooms, garages, and workshops where the largest portable charge is required.



- 55A 233B C on a 9 kg charge
- Metal hook wall hanger on every unit
- Boiler rooms, garages, and workshops
- 2 years from date of manufacture

SPECIFICATIONS

Manufacturer model	GP-9x ABC/MP	Dimensions	588 mm high, 185 mm cylinder diameter
Fire rating	55A 233B C	Gross weight	14 kg
Capacity	9 kg	Mounting	Metal hook wall hanger included
Extinguishing medium	FUREX S ABC	Warranty	2 years from date of manufacture
Standard	EN 3-7 (CNBOP-PIB approved)	Manufacture	Manufactured in Poland
Operating temperature	-30 °C to +60 °C	Article number	NV-FE-109
Electrical safety	Live equipment to 1000 V	EAN	5907620602346

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY			
8424.10	EXW · FCA · DAP	CE	EN 3-7	CNBOP-PIB	ISO 9001

PRODUCT OVERVIEW

Polish-manufactured stored-pressure ABC powder extinguisher from OGNIOCHRON S.A., model GP-9x ABC/MP, sized for boiler rooms, garages, and home workshops where buyers need the highest practical powder rating in a portable they can operate without specialist training. The 9 kg FUREX S ABC charge is rated 55A 233B C under EN 3-7 with CNBOP-PIB approval, approved for live electrical equipment up to 1000 V, and operates from -30 °C to +60 °C. Each unit ships with a metal hook wall hanger so it can be fixed at the hazard point rather than left on the floor. At 14 kg gross weight and 588 mm high it is the largest standard portable in the domestic and light workplace range for plant rooms and utility areas where a smaller cylinder would not meet the calculated rating or discharge duration.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

