

PORTABLE FIRE EXTINGUISHERS

CO2 Fire Extinguisher,
2 kg, with UDT Permit

2 kg CO2 snow extinguisher rated 34B under EN 3-7 with CNBOP-PIB approval and a UDT operating permit, for offices, server rooms, and electronics bays where powder residue would damage sensitive equipment.



- 34B on a 2 kg CO2 charge
- No powder or foam residue after use
- Metal wall hanger with strap in the box
- Live equipment to 1000 V

SPECIFICATIONS

Manufacturer model	GS-2x B	Dimensions	543 mm high, 105 mm cylinder diameter
Fire rating	34B	Gross weight	7 kg
Capacity	2 kg	Colour	Red cylinder, red handle, black horn
Extinguishing medium	CO2	Mounting	Metal wall hanger with strap included
Standard	EN 3-7 (CNBOP-PIB approved, UDT permit)	Warranty	2 years from date of manufacture
Operating temperature	-30 °C to +60 °C	Manufacture	Manufactured in Poland
Electrical safety	Live equipment to 1000 V	Article number	NV-FE-CO2B

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY			
8424.10	EXW · FCA · DAP	CE	EN 3-7	CNBOP-PIB	ISO 9001

PRODUCT OVERVIEW

Polish-manufactured CO2 fire extinguisher from OGNIОCHRON S.A., model GS-2x B, sized for offices, computer rooms, electronics workshops, and plant bays where buyers need residue-free suppression on flammable liquids and energised equipment without powder contamination. The 2 kg liquefied CO2 charge is rated 34B under EN 3-7 with CNBOP-PIB approval and ships with a UDT operating permit required for registration in Poland. It is approved for live electrical equipment to 1000 V, operates from -30 °C to +60 °C, and leaves no dry powder or foam residue after discharge. Each unit ships with a red metal wall hanger and black securing strap. At 7 kg gross weight and 543 mm high it is the compact EN 3-7 CO2 portable for desks, server racks, and electrical cabinets where a 5 kg cylinder would not fit the mounting point.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

