

PORTABLE FIRE EXTINGUISHERS

Liquid Fire Extinguisher, 2 L ABF

Stored-pressure 2 L ABF liquid cylinder rated 8A 55B 40F under EN 3-7 with CNBOP-PIB approval, for kitchens and living rooms where foam solution can extinguish cooking fats and flammable liquids without powder residue.



- 8A 55B 40F on a 2 L ABF charge
- Class F cover for cooking fats and oils
- Red metal basket wall hanger in the box
- 368 mm high, 3.5 kg, red EN 3-7 cylinder

SPECIFICATIONS

Manufacturer model	GPN-2x ABF/M	Gross weight	3.5 kg
Fire rating	8A 55B 40F	Colour	Red cylinder and base
Capacity	2 L	Mounting	Red metal basket wall hanger included
Extinguishing medium	1.56 L water + 0.4 L FUREX A + 0.04 L AFFF cartridge	Warranty	2 years from date of manufacture
Standard	EN 3-7 (CNBOP-PIB approved)	Manufacture	Manufactured in Poland
Operating temperature	+5 °C to +60 °C	Article number	NV-FE-L2A
Electrical safety	Live equipment to 1000 V	EAN	5907620600304
Dimensions	368 mm high, 110 mm cylinder diameter		

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY			
8424.10	EXW · FCA · DAP	CE	EN 3-7	CNBOP-PIB	ISO 9001

PRODUCT OVERVIEW

Polish-manufactured stored-pressure ABF liquid extinguisher from OGNIOPHON S.A., model GPN-2x ABF/M, sized for kitchens, living rooms, and light offices where buyers need Class F cover for cooking fats alongside Class A solids and Class B liquids without the collateral damage of ABC powder. The 2 L charge combines demineralized water, FUREX A, and a FUREX AFFF cartridge, rated 8A 55B 40F under EN 3-7 with CNBOP-PIB approval, approved for live electrical equipment up to 1000 V, and operates from +5 °C to +60 °C. Each unit ships with a red metal basket wall hanger. At 3.5 kg gross weight and 368 mm high it is the compact EN 3-7 liquid portable for domestic kitchens and small gastronomy bays where a 6 L cylinder would be oversized.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

