

PORTABLE FIRE EXTINGUISHERS

Liquid Fire Extinguisher, 3 L ABF

Stored-pressure 3 L ABF liquid cylinder rated 13A 89B 40F under EN 3-7 with CNBOP-PIB approval, for kitchens, offices, and light workplaces where foam solution can extinguish cooking fats and flammable liquids without powder residue.



- 13A 89B 40F on a 3 L ABF charge
 - Class F cover for cooking fats and oils
- Silver metal wall hanger in the box
 - 412 mm high, 4.8 kg, red EN 3-7 cylinder

SPECIFICATIONS

Manufacturer model	GPN-3x ABF	Gross weight	4.8 kg
Fire rating	13A 89B 40F	Colour	Red cylinder, black base
Capacity	3 L	Mounting	Silver metal wall hanger included
Extinguishing medium	2.34 L demineralized water + 0.6 L Furex A + 0.06 L Furex AFFF cartridge	Warranty	2 years from date of manufacture
Standard	EN 3-7 (CNBOP-PIB approved)	Manufacture	Manufactured in Poland
Operating temperature	+5 °C to +60 °C	Article number	NV-FE-L3A
Electrical safety	Live equipment to 1000 V	EAN	1GPN303000-001
Dimensions	412 mm high, 125 mm cylinder diameter		

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY			
8424.10	EXW · FCA · DAP	CE	EN 3-7	CNBOP-PIB	ISO 9001

PRODUCT OVERVIEW

Polish-manufactured stored-pressure ABF liquid extinguisher from OGNIОCHRON S.A., model GPN-3x ABF, sized for kitchens, offices, boiler rooms, and workshops where buyers need Class F cover for cooking fats alongside Class A solids and Class B liquids without the collateral damage of ABC powder. The 3 L charge combines demineralized water, Furex A, and a Furex AFFF cartridge, rated 13A 89B 40F under EN 3-7 with CNBOP-PIB approval, approved for live electrical equipment up to 1000 V, and operates from +5 °C to +60 °C. Each unit ships with a silver metal wall hanger. At 4.8 kg gross weight and 412 mm high it sits between the supplementary domestic 2 L line and the 6 L full workplace cylinder for buyers who want a calculated EN rating in a lighter kitchen or office portable.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

