

PORTABLE FIRE EXTINGUISHERS

Liquid Fire Extinguisher,
6 L AB Fluorine-Free

Stored-pressure 6 L fluorine-free AB liquid cylinder rated 27A 144B under EN 3-7 with CNBOP-PIB approval, for offices, boiler rooms, and workshops where a mid-size foam portable is needed without PFAS in the agent.



- 27A 144B on a 6 L fluorine-free AB charge
- FFX150 agent without PFAS fluorine compounds
- Silver metal hook wall hanger in the box
- Offices, boiler rooms, and workshops

SPECIFICATIONS

Manufacturer model	GPN-6x AB/FF	Gross weight	9.4 kg
Fire rating	27A 144B	Colour	Red cylinder, green base and nozzle
Capacity	6 L	Mounting	Silver metal hook wall hanger included
Extinguishing medium	6 L FFX150 fluorine-free AB foam solution	Warranty	2 years from date of manufacture
Standard	EN 3-7 (CNBOP-PIB approved)	Manufacture	Manufactured in Poland
Operating temperature	0 °C to +60 °C	Article number	NV-FE-L6F
Electrical safety	Live equipment to 1000 V	EAN	5907620602490
Dimensions	502 mm high, 160 mm cylinder diameter		

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY			
8424.10	EXW · FCA · DAP	CE	EN 3-7	CNBOP-PIB	ISO 9001

PRODUCT OVERVIEW

Polish-manufactured stored-pressure fluorine-free AB liquid extinguisher from OGNIОCHRON S.A., model GPN-6x AB/FF, sized for offices, schools, warehouses, workshops, and domestic premises where buyers need Class A solids and Class B liquids covered by a single portable without ABC powder residue. The 6 L FFX150 fluorine-free foam solution is rated 27A 144B under EN 3-7 with CNBOP-PIB approval, approved for live electrical equipment up to 1000 V, and operates from 0 °C to +60 °C. Each unit ships with a silver metal hook wall hanger. At 9.4 kg gross weight and 502 mm high it suits buyers who need a calculated EN rating across offices, garages, and storage areas without switching to dry powder.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

