

PORTABLE FIRE EXTINGUISHERS

Liquid Fire Extinguisher, 6 L AB

Stored-pressure 6 L AB liquid cylinder rated 21A 183B under EN 3-7 with CNBOP-PIB approval, for offices, boiler rooms, and workshops where foam solution can extinguish solids and flammable liquids without powder residue.



- 21A 183B on a 6 L AB charge
 - Offices, boiler rooms, and workshops
- Metal hook wall hanger in the box
 - Foam solution easier to clean up than powder

SPECIFICATIONS

Manufacturer model	GPN-6x AB	Gross weight	9.3 kg
Fire rating	21A 183B	Colour	Red cylinder, black base
Capacity	6 L	Mounting	Metal hook wall hanger included
Extinguishing medium	5.91 L demineralized water + 0.09 L BOAL AFFF compact	Warranty	2 years from date of manufacture
Standard	EN 3-7 (CNBOP-PIB approved)	Manufacture	Manufactured in Poland
Operating temperature	+5 °C to +60 °C	Article number	NV-FE-L6B
Electrical safety	Live equipment to 1000 V	EAN	5907620600380
Dimensions	502 mm high, 160 mm cylinder diameter		

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY			
8424.10	EXW · FCA · DAP	CE	EN 3-7	CNBOP-PIB	ISO 9001

PRODUCT OVERVIEW

Polish-manufactured stored-pressure AB liquid extinguisher from OGNIОCHRON S.A., model GPN-6x AB, sized for offices, boiler rooms, garages, and workshops where buyers need Class A solids and Class B liquids covered without the collateral damage of ABC powder. The 6 L charge combines demineralized water with a BOAL AFFF compact cartridge, rated 21A 183B under EN 3-7 with CNBOP-PIB approval, approved for live electrical equipment up to 1000 V, and operates from +5 °C to +60 °C. Each unit ships with a metal hook wall hanger. At 9.3 kg gross weight and 502 mm high it is the standard mid-size liquid portable for domestic utility rooms, offices, and light industrial bays where a calculated EN rating is required without switching to dry powder.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

