

PORTABLE FIRE EXTINGUISHERS

Liquid Fire Extinguisher, 6 L ABF

Stored-pressure 6 L ABF liquid cylinder rated 21A 233B 40F under EN 3-7 with CNBOP-PIB approval, for offices, boiler rooms, and kitchens where foam solution can extinguish cooking fats and flammable liquids without powder residue.



- 21A 233B 40F on a 6 L ABF charge
- Class F cover for cooking fats and oils
- Metal hook wall hanger in the box
- Foam solution easier to clean up than powder

SPECIFICATIONS

Manufacturer model	GPN-6x ABF/MP	Gross weight	9.5 kg
Fire rating	21A 233B 40F	Colour	Red cylinder, black base
Capacity	6 L	Mounting	Metal hook wall hanger included
Extinguishing medium	5.91 L demineralized water + 0.09 L Furex AFFF cartridge	Warranty	2 years from date of manufacture
Standard	EN 3-7	Manufacture	Manufactured in Poland
Operating temperature	+5 °C to +60 °C	Article number	NV-FE-L6A
Electrical safety	Live equipment to 1000 V	EAN	5907620601165
Dimensions	502 mm high, 160 mm cylinder diameter		

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY			
8424.10	EXW · FCA · DAP	CE	EN 3-7	CNBOP-PIB	ISO 9001

PRODUCT OVERVIEW

Polish-manufactured stored-pressure ABF liquid extinguisher from OGNIОCHRON S.A., model GPN-6x ABF/MP, sized for offices, boiler rooms, garages, kitchens, and workshops where buyers need Class F cover for cooking fats alongside Class A solids and Class B liquids without the collateral damage of ABC powder. The 6 L charge combines demineralized water with a Furex AFFF cartridge, rated 21A 233B 40F under EN 3-7 with CNBOP-PIB approval, approved for live electrical equipment up to 1000 V, and operates from +5 °C to +60 °C. Each unit ships with a metal hook wall hanger. At 9.5 kg gross weight and 502 mm high it is the largest liquid portable in the domestic and light workplace range and suits buyers who need a calculated EN rating beside a fireplace, barbecue, or commercial kitchen without switching to dry powder.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

