

FIRE EXTINGUISHERS

Liquid Fire Extinguisher,
9 L Water with Additive

Stored-pressure 9 L water-with-additive cylinder rated 55A under EN 3, for shops, assembly halls, and public buildings where liquid media avoids powder residue and keeps evacuation routes visible.



- 55A Class A on a 9 L water charge
- Shops, assembly halls, and corridors
- Liquid discharge without powder obscuring exits
- Water-based agent easier to clean than powder

SPECIFICATIONS

Fire rating	55A	Dimensions	525 mm high, 180 mm cylinder diameter
Capacity	9 L	Gross weight	14 kg
Extinguishing medium	7.2 L water + 1.8 L Inilam AX wetting agent	Material	Cold-rolled steel cylinder (DC01/ST12)
Standard	EN 3	Colour	Red cylinder, black hose and nozzle
Pressure	15 bar at 20 °C (nitrogen propellant, 18 bar PS)	Manufacture	Manufactured in Sweden
Operating temperature	+5 °C to +60 °C	Article number	NV-FE-L9W

ORDERING AND DELIVERY

HS CODE	INCOTERMS	CONFORMITY
8424.10	EXW · FCA · DAP	CE EN 3

PRODUCT OVERVIEW

Swedish-manufactured stored-pressure water extinguisher with Inilam AX wetting agent, sized for retail floors, assembly halls, corridors, and other public spaces where buyers want Class A cover without the residue and visibility loss of ABC powder. The 9 L charge combines 7.2 L water with 1.8 L Inilam AX additive, rated 55A under EN 3, nitrogen-pressurised to 15 bar at 20 °C, and operates from +5 °C to +60 °C. At 14 kg gross weight and 525 mm high it is a high-capacity Class A portable for premises where powder fallout would litter stock or obscure exit signage during discharge.

Values are the declared specifications for each article and are confirmed against the delivered batch on the order confirmation.

